



Brief Introduction

CR9310/20 series withstanding voltage/insulation resistance tester is an economical and intelligent safety tester with the characteristics of small size, light weight, pleasing appearance and easy operation.

CR9310/20 series can be widely used in the safety tests of household appliances, transformer, electrical equipment's and components.

Features

- **CR9310** series: AC:5kV/10mA; DC:6kV/5mA AC/ DC withstanding voltage/insulation resistance tester
- **CR9320** series: AC:5kV/20mA; DC:6kV/10mA AC/ DC withstanding voltage/insulation resistance tester
- **CR9310/20** AC/ DC withstanding voltage/insulation resistance tester
- CR9310A/20A: AC / DC withstanding voltage tester
- CR9310B/20B: AC withstanding voltage tester
- 480×272 dot-matrix, TFT-LCD display
- Rapidly discharging and arc detection
- Randomly set voltage rising time and testing time in 999.9 seconds;
- Freely set waiting time for insulation resistance
- Hold 5 testing steps; 4 testing modes selectable
- Brand new operation interface and concise interface operation design
- Lock keyboard
- PLC interface

Specifications

Model		CR9310/20	CR9310A/20A	CR9310B/20B
Withstanding voltage test				
Output voltage	AC	0.05 —5.00kV ± (2% reading+5digits) , (50Hz、 60Hz optional)		
	DC	0.05 —6.00kV ± (2% reading+5digits)		
	Voltage adjustment rate	≤ (1% - 5V) (rated power)		
Current test range	AC	CR9310: 0.000mA – 10.00mA ±(2% reading+2digits)		
		CR9320: 0.000mA – 20.00mA ±(2% reading+2digits)		
	DC	CR9310: 0uA – 5.00mA ±(2% reading+2digits)		
	Discharge function	CR9320: 0uA –10.00mA ±(2% reading+2digits)		
		Discharge after test ends (DCW)		
Insulation resistance test				
Output voltage		0.10kV – 1.00kV ±(2%reading+2V)		
Resistance test range		1MΩ– 9999MΩ		
Resistance test accuracy	500V-1000V	1MΩ– 1000MΩ ±(5%reading+2digits) 1000MΩ–9999MΩ ±(10%reading+2digits)		
	100V-500V	1MΩ– 1000MΩ ±(10%reading+2digits)		
Discharge function		Discharge after test ends		
Arc detection				
Measurement range	AC	1 – 9 levels (factory default 5) (20mA、 18mA、 16mA、 14mA、 12mA、 10mA、 7.7mA、 5.5mA、 2.8mA respectively)		
	DC	1 – 9 levels		
General specification				
Memory		5 groups		
Voltage rising time		0.1s – 999.9s		
Test time setting (AC/DC)		0.2s – 999.9s		
Waiting time (IR)		0.2s – 999.9s		
Time Accuracy		±(1%+0.1s)		
Dimension (W×H×D)		280mm×89mm×428mm/10kg		
Interface				
Standard		HANDLER, RS232, USBDRV(PC interface), USBHOST(USB port)		